



**TIL DURAIN INHERENT FR ECOGREEN  
JACKET - 200g/m2**  
(Modacrylic/Lycocell/Para-Aramid/Static-Control)

TIL WORKWEAR Flame Retardant Inherent FR Jacket and Trousers are constructed with 50% Sustainable Ecogreen materials that meet and exceed safety standards. Designed for maximum comfort, durability and protection against heat, flame, Electric Arc and chemical liquids with High Visibility Colours.

### GARMENT FEATURES:

- Adjustable waistband
- Two Large side pockets
- Wide FR Reflective Striping around arms and shoulders.
- Concealed press button on cuffs
- Concealed one-way black high-density zip with brass snap closure
- Sleeve tool pocket
- Two Radio Loops
- Bar Tack at all Stress points adding strength
- Left & Right Chest Pocket with concealed inner access thru-way pocket.







**TIL DURAIN INHERENT FR ECOGREEN  
TROUSER- 200g/m2**  
(Modacrylic/Lycocell/Para-Aramid/Static-Control)





### GARMENT FEATURES:

- Comfort fit
- 2 Side pockets
- 2 back pocket closed with snap buttons
- Stitched with FR Aramid threads
- Bar tack reinforcement at all the stress points
- Elastic waist band adding flexibility and comfort
- FR 50MM Reflective tapes on legs
- Belt loops 2

## Ecogreen

TECHNICAL DATA	TIL WORKWEAR	TEST METHOD
Product Code	DRFR200JT	
Width	150 cm (+2/-1 cm)	ISO 3801: 1978
Weight	200 g/m <sup>2</sup> (± 5%)	ISO 3932: 1980
Composition	Modacrylic/lyocell/para-aramid/Static-Control <sup>TM</sup>	
Construction	2/1 twill	
Available finishes	Standard: Comfort. Optional: Hydro-Tec	

Physical performance		
Tensile strength	750 N x 500 N (± 10%)	ISO 13934-1: 1999
Tear strength	40 N x 30 N (± 10%)	NEN-EN-ISO 13937-2:2000
Care labelling		
Domestic laundering		
Industrial laundering	75 °C Colour:      White: 	
PPE requirements*	 optional: 	

CERTIFICATION		
	Industrial flame & heat hazards	EN ISO 11611, 11612 A1, A2, B1, C1, E1, F1: 2015 (A1 + A2= 100 x ISO 15797 - 75°C)
	Short-duration thermal exposures from fire	NFPA 2112: 2018
	Electric Arc	<i>Single Layer:</i> EN IEC 61482-1-2, class 1; 2015 HRC/Category 1 (4 ≤ ATPV ≥ 8 cal/cm <sup>2</sup> ) <i>System:</i> XL9200 + XL9240 EN IEC 61482-1-2; 2015 class 2 (7kA) <i>System:</i> HRC/Category 2 (8 ≤ ATPV ≥ 25 cal/cm <sup>2</sup> )
	Anti-Static for explosion risk	EN 1149-5: 2018, EN 1149-3: 2004
	Liquid chemicals**	EN 13034: 2005 + A1: 2009
	Contrast colours: Delftblue 89249, Twilight 89250	EN ISO 20471: 2013
	General requirements***	EN ISO 13688: 2013
	Öko-Tex Standard 100, class 2	Centexbel, no. 0903009

### COLOURS

Twilight 89250	Black velvet 89254	Mooncrust 89253	Interior blue 89350	Delft blue 89249	Ribbon Red 89252	Sunrise Orange 89305	Yellow (EN20471) 89251
-------------------	-----------------------	--------------------	------------------------	---------------------	---------------------	-------------------------	------------------------------



Contact us:  
[sales@tilworkwear.com](mailto:sales@tilworkwear.com)  
[www.tilworkwear.com](http://www.tilworkwear.com)



This fabric is an  
UL certified product:



All mentioned data must be considered as indicative values. To the best of our knowledge all information contained herein is accurate. TIL WORKWEAR Jacket and Trousers declines any form of liability related to the use of the attached specimen that shall be regarded as a sample only and therefore not meant to be used in any form of garment making.