

**TIL DURAIN INHERENT FR NOMEX IIIA  
COVERALL - 220g/m2**  
(Modacrylic/Lyocell/Para-Aramid/Static-Control)



Size Range: 36-38(S), 40-42(M), 44-46(L), 48-50(XL), 52-54(2XL)



*SAFE, TIL the very last task.*



**EXTREME TEAR STRENGTH**

TIL Workwear Protective Fabrics proprietary Gridstrong technology provides an unmatched tear strength to ensure a long-lasting performance in tough environments.

**GUARANTEED COMFORT  
IN ANY SITUATION**

Soft, silky natural fibres provide superior moisture management, keeping you comfortable, cool and dry at all times thanks to constant breathability.

**OUTSTANDING AFTER-  
WASH APPEARANCE**

Colourfastness rating of 4-5 after 100+ industrial washing cycles (ISO 15797).

**GARMENT  
FEATURES:**

- Turn Down Collar
- Front Closure Flame Retardant Metal Zipper and Snap Buttons
- 2 Chest Pockets Closed With FR Metal Zipper
- 2 Back Pockets With FR Snap Buttons
  - Stitched With FR Threads Ensuring Durability
- Bar Tack at all Stress Points Adding Strength
- Elastic Waistband Adding Flexibility and Comfort
- Cuffs With Snap Closures
- 50mm FR Reflective Tape on Shoulders, Sleeves, and Legs
- 2 Side Swing Pockets With Fabric and Inner Access Openings
  - Hanging Loops
- 1 Ruler Pocket on Trousers
- 1 Sleeve Pocket With Flap and Velcro Closure



EN ISO 11612  
A1 A2 B1 C1 F1



EN 61482-1-2  
Class -1













EN 1149-5



## NOMEX IIIA

TECHNICAL DATA	TIL WORKWEAR	TEST METHOD
Product Code	DRFR200C	
Width	150 cm (+2/-1 cm)	ISO 3801: 1978
Weight	220 g/m <sup>2</sup> (± 5%)	ISO 3932: 1980
Composition	Modacrylic/lyocell/para-aramid/Static-Control™	
Construction	2/1 twill	
Available finishes	Standard: Comfort. Optional: Hydro-Tec	

Physical performance		
Tensile strength	750 N x 500 N (± 10%)	ISO 13934-1: 1999
Tear strength	40 N x 30 N (±10%)	NEN-EN-ISO 13937-2:2000
Care labelling		
Domestic laundering		
Industrial laundering	75 °C Colour: White: 	
PPE requirements*	 optional: 	

CERTIFICATION		
	Industrial flame & heat hazards	EN ISO 11611, 11612 A1, A2, B1, C1, E1, F1: 2015 (A1 + A2= 100 x ISO 15797 - 75°C)
	Short-duration thermal exposures from fire	NFPA 2112: 2018
	Electric Arc	<i>Single Layer:</i> EN IEC 61482-1-2, class 1; 2015 HRC/Category 1 (4 ≤ ATPV ≥ 8 cal/cm²) <i>System:</i> XL9200 + XL9240 EN IEC 61482-1-2; 2015 class 2 (7kA) <i>System:</i> HRC/Category 2 (8 ≤ ATPV ≥ 25 cal/cm²)
	Anti-Static for explosion risk	EN 1149-5: 2018, EN 1149-3: 2004
	Liquid chemicals**	EN 13034: 2005 + A1: 2009
	Contrast colours: Delftblue 89249, Twilight 89250	EN ISO 20471: 2013
	General requirements***	EN ISO 13688: 2013
	Öko-Tex Standard 100, class 2	Centexbel, no. 0903009

### COLOURS

Twilight 89250	Black velvet 89254	Mooncrust 89253	Interior blue 89350	Delft blue 89249	Ribbon Red 89252	Sunrise Orange 89305	Yellow (EN20471) 89251
-------------------	-----------------------	--------------------	------------------------	---------------------	---------------------	-------------------------	------------------------------

 **TIL WORKWEAR**

Contact us:  
sales@tilworkwear.com  
www.tilworkwear.com



This fabric is an  
UL certified product:



All mentioned data must be considered as indicative values. To the best of our knowledge all information contained herein is accurate. TIL WORKWEAR Coverall declines any form of liability related to the use of the attached specimen that shall be regarded as a sample only and therefore not meant to be used in any form of garment making.